TVT

Secure The World With You


CAMERA

TD-9482E3B-DP

8MP Dual-lens Splicing Bullet Network Camera



- H.265+/H.265/H.264+/H.264/MJPEG coding
- Max.resolution: 8MP (4640 × 1760)
- ICR auto switch, true day / night vision
- Support smart supplement light
- Up to 30 m IR night view distance; up to 20m white light distance
- 3D DNR, WDR, HLC, BLC and ROI coding
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- IP66 protection grade
- Support three streams
- Support mobile surveillance by smart phones with iOS and Android OS
- Support SMD
- Support NAT function
- Multiple smart events can be enabled at the same time
- Blue and red light warning (flashing alternately)
- Support user-defined warning voice import
- Dual system backup



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Fax: +86-755-33104777

Web site: http://en.tvt.net.cn

E-mail: overseas@tvt.net.cn

TD-9482E3B-DP

8MP Dual-lens Splicing Network Camera

SPECIFICATIONS

Specifications \ Model	TD-9482E3B-DP
Camera	
Image Sensor	1 / 2.7 " Progressive Scan CMOS × 2
Max. Resolution	4640×1760
Electronic Shutter	1 / 3 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.0032 lux@F1.6, AGC ON; 0 lux with LED ON
Lens	2.8mm @F1.6
Field of View	Horizontal: 180°; Vertical:66°
Lens Mount	M12
Day & Night	Auto
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Defog	Yes
S/N Ratio	⩾50dB
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	8MP (4640×1760), 6MP(3632×1632), 4MP(3200×1200), 2MP (2304×864), 2048×768, 1600×608, 1200×448, 960×368, 640×240
Main Stream	8MP/6MP/4MP/2MP(60Hz : 1~30fps; 50Hz : 1~25fps)
Sub Stream	2048×768/1600×608/1200×448(60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)
Third Stream	1200×448/960×368/640×240(60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)
Bit Rate	64 Kbps ~10Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45 (10/100 Base-T)
Video Output	No
Audio	1CH audio input; 1CH audio output; 1CH built-in speaker; 2CH built-in MICs
Storage	Built-in micro SD card slot; up to 256GB
Reset	Yes
Alarm	1CH alarm input; 1CH alarm output
Intelligent Analytics	
Intelligent Video Detection (IVD)	Line crossing, region intrusion/entrance/exiting (human/vehicle classification), loitering detection, illegal parking detection, abandoned/missing object detection
Statistics	Target counting by line/area, heat map
Exception Detection	Scene change, video blur and abnormal color detection, audio exception
Face Detection	Face detection and face capture
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 4 motor vehicle features and 1 non-motor vehicle feature


DORI Distance

Lens	Detect	Observe	Recognize	Identify
2.8mm	54m(178ft)	22m(71ft)	11m(36ft)	5m(18ft)

Functions	
Remote Monitoring	Web Browser/NVMS/NVR/mobile APP
Web Browser	Chrome 105.0+/Edge 105.0+/Firefox 121.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission

Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, HTTP POST/GET, 802.1x, UPnP, HTTPS, NAT, QoS
Interface Protocol	ONVIF
API&SDK	Yes
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, Network disconnection, sensor alarm, audio alarm, light alarm
General Function	Watermark, video mask, heartbeat, smart supplement light, ANR, cloud upgrade, disarming
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and token authentication for HTTP/RTSP/API
PoE	Yes , IEEE802.3af
Supplement Light Range	IR Range: up to 30m; White light range: up to 20m
Ingress Protection	IP66
Others	
Power Supply	DC12V/PoE
Power Consumption	PoE: max. 10.2W; DC12V: max. 9W
Storage Conditions	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	225.9 × 102.3 × 85.8
Weight (net)	Approx.0.906KG
Installation	Ceiling mounting; Wall mounting
Material	Aluminum alloy body
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS




AVAILABLE MODEL


Available Model	TD-9482E3B-DP (D / PE / AW3)

*All pictures and specifications are for reference only and are subject to change without prior notice.


AVAILABLE ACCESSORIES



TD-YXH0301




TD-YXH0103



TD-YXH0104



TD-YXH0304



TD-YXH0205



TD-YXH0301+
TD-YZJ0501



TD-YXH0301+
TD-YZJ0601



TD-YXH0301+
TD-YZJ0810

*All pictures and specifications are for reference only and are subject to change without prior notice.