


TD-9482S4-C

8MP Dual Illumination Water-proof Bullet Network Camera



- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution: 8MP (3840 × 2160)
- Auto day/night switch
- 3D DNR, HWDR, HLC, BLC, Defog, etc.
- ROI coding
- Support smart supplement light
- 30~40m white light view distance; 30~50m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support NAT function
- Support SMD
- Support line crossing detection, region intrusion detection, abandoned/missing object detection, video exception detection
- Dual-system backup



en.tvt.net.cn


For more information, please visit our website

SPECIFICATIONS

Model	TD-9482S4-C	
Camera		
Image Sensor	1 / 2.8 "CMOS	
Image Size	3840×2160	
Electronic Shutter	1 / 3s ~ 1 / 100000s	
Iris Type	Fixed Iris	DC Iris
Min. Illumination	0.02 lux @F1.6, AGC ON; 0 lux with illumination on	
Lens	2.8mm@F1.6, H.FoV: 106°; V.FoV: 57°; D.FoV: 124° 3.6mm@F1.6, H.FoV: 90°; V.FoV: 47°; D.FoV: 107°	2.8~12mm@F1.6, H.FoV: 97.3°~34°; V.Fov: 52.3°~17.7°; D.FoV: 116°~37°
Focus	Fixed	Motorized
Lens Mount	M12	Φ14
Day&Night	ICR	
Wide Dynamic Range	120dB	
BLC	Yes	
HLC	Yes	
Digital NR	Yes	
Defog	Yes	
S/N Ratio	≥50dB	
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°;Rotation: 0°~360°	
Image		
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub /Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG	
H.265 Compression Standard	Main Profile@Leve4.1 High Tier	
Resolution	8MP(3840×2160),6MP(3200×1800),4MP(2688×1520),2K(2560×1440),1080P(1920×1080),720P(1280×720),D1,VGA(640×480),640×360,480×240,CIF	
Main Stream	8MP(1~20fps)/6MP/4MP/2K/1080P(60Hz: 1~30fps;50Hz: 1~25fps)	
Sub Stream	1080P(60Hz:1~15fps;50Hz:1~12fps)/720P/D1/VGA/640×360/CIF/480×240(60Hz: 1~30fps;50Hz: 1~25fps)	
Third Stream	720P/D1/640×360/CIF(60Hz: 1~30fps;50Hz: 1~25fps)	
Bit Rate	64 Kbps ~ 12Mbps	
Bit Rate Type	VBR / CBR	
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser	
Audio Compression	G711A/U	
ROI	Each ROI to be configured separately	
Interfaces		
Network	RJ45 (10/100 Base-T)	
Video Output	No	
Audio	1CH audio input; 1CH built-in MIC	
Storage	Built-in micro SD card slot, up to 256GB	
Reset	Yes	
Functions		
Remote Monitoring	Web browser /TVT NVR/NVMS2.X/Mobile APP	
Web Browser	Chrome 105.0+/Edge 105.0+/Firefox 121.0+/Safari 14.0+	
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission	
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, NAT, QoS	
Interface Protocol	ONVIF	
Storage	Network remote storage; micro SD card storage	
API&SDK	Yes	
Smart Alarm	Motion detection, SMD, SD card full, SD card error, IP address conflict, cable disconnection, video exception (scene change, video blur and abnormal color detection)	
Smart Event	Line crossing /region intrusion detection(human/vehicle classification), abandoned/missing object detection	
General Function	Watermark, IP address filtering, video mask, heartbeat, smart supplement light, corridor pattern, image distortion correction, ANR, cloud upgrade, disarming	
PoE	Yes (IEEE802.3af)	
Supplement Light Range	IR range: 30 ~ 50 m; white light range:30 ~ 40 m	
Ingress Protection	IP67	

Security	Video encryption, firmware encryption, configuration encryption, illegal loginbck, P address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP/API			
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8mm	79m(259ft)	32m(105ft)	16m(52ft)	8m(27ft)
3.6mm	99m(325ft)	40m(130ft)	20m(68ft)	10m(34ft)
2.8~12mm(W)	88m(288ft)	35m(114ft)	17m(56ft)	8m(27ft)
2.8~12mm(T)	277m(908ft)	111m(364ft)	55m(180ft)	28m(91ft)
Others				
Power Supply	DC12V/PoE			
Power Consumption	DC12V:<9.3W; PoE: <11.2W			
Storage Conditions	- 30 °C ~ 65 °C (-22°F~149°F), Humidity: less than 95 % (non-condensing)			
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)			
Dimensions (mm)	217.6 × 80.5 × 80.3			
Material	Aluminum alloy body			
Weight (net)	Approx. 0.68KG			
Installation	Ceiling mounting; wall mounting			
Certificate	CE, FCC			
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)			

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-9482S4-C(D/PE/AW3)	Fixed lens
	TD-9482S4-C(D/AZ/PE/AW3)	Motorized lens